

DATE _____

FLOW RELAY [Model SP-RX] INQUIRY CHECKSHEET

Please inform us of the following conditions in detail as much as possible when you make reference to flow relay.

In case of replacing existing flow relay, please describe the serial number inscribed on the nameplate.

Serial number is figures beginning with "7" or "7M".

e.g. MFG № 795081

MFG № 7M15157

MFG № 789652A2

NEW or REPLACEMENT	<input type="checkbox"/> NEW <input type="checkbox"/> REPLACEMENT		
MANUFACTURING № (In case of replacement)	MFG №7 _____		
MODEL	<input type="checkbox"/> SP-RX (d2G4) Flameproof packing type <input type="checkbox"/> SP-RXC (d2G4) Wiring pipe pull-in type <input type="checkbox"/> SP-REX (Exd II CT4) Flameproof packing type <input type="checkbox"/> SP-REXC(Exd II CT4) Wiring pipe pull-in type		
DIAMETER	<input type="checkbox"/> 15A <input type="checkbox"/> 20A <input type="checkbox"/> 25A <input type="checkbox"/> 32A <input type="checkbox"/> 40A <input type="checkbox"/> 50A <input type="checkbox"/> 65A <input type="checkbox"/> 80A <input type="checkbox"/> 100A <input type="checkbox"/> 125A <input type="checkbox"/> ()A		
FLANGE STANDARDS	<input type="checkbox"/> JIS10K <input type="checkbox"/> JIS5K <input type="checkbox"/> ANSI150lb <input type="checkbox"/> JPI150lb <input type="checkbox"/> OTHERS()		
FLANGE FACES	<input type="checkbox"/> FF <input type="checkbox"/> RF <input type="checkbox"/> SERRATION <input type="checkbox"/> OTHERS()		
FLOW DIRECTION	<input type="checkbox"/> HORIZONTAL <input type="checkbox"/> UPWARD <input type="checkbox"/> DOWNWARD		
LIQUID	<input type="checkbox"/> CLEAR WATER <input type="checkbox"/> INDUSTRIAL WATER <input type="checkbox"/> RIVER WATER <input type="checkbox"/> TURBINE OIL <input type="checkbox"/> SEA WATER <input type="checkbox"/> OTHERS() ※Please describe the liquid quality in detail. ※Please describe corrosivity, viscosity, volatility, solubility and inflammability of the liquid.		
LIQUID TEMPERATURE	°C		
LIQUID PRESSURE	MPa		
LIQUID SPECIFIC GRAVITY			
NORMAL FLOWRATE	l/min		
MAX FLOWRATE	l/min		
OPERATING QUANTITY OF FLOW	<input type="checkbox"/> DECREASE <input type="checkbox"/> INCREASE l/min		
MATERIAL (The combination of the right)	ELEMENT		BODY
	<input type="checkbox"/>	SUS304	FC200
	<input type="checkbox"/>	SUS304	SCS13
	<input type="checkbox"/>	SUS316	SCS14
	<input type="checkbox"/>	OTHERS()	OTHERS()
BODY COLOUR	<input type="checkbox"/> STANDARD MUNSELL 7.5BG4/1.5 BAKING FINISH (It is a standard color in a case that body material is FC200.) ※Coating is not performed in a case that body material is SCS, however, terminal housing part is coated by MUNSELL7.5BG4/1.5 baking. <input type="checkbox"/> OTHERS()		
CONTACT RATING (AC60VA,DC30W)	<input type="checkbox"/> AC V A <input type="checkbox"/> DC V A		
ACCESSORIES	<input type="checkbox"/> NO NEED		
	<input type="checkbox"/>	NEED	<input type="checkbox"/> THREADED FLANGES (with BOLTS,NUTS&PACKINGS) <input type="checkbox"/> FCD <input type="checkbox"/> SUS304 <input type="checkbox"/> SUS316 <input type="checkbox"/> OTHERS() <input type="checkbox"/> WELDING FLANGES (with BOLTS,NUTS&PACKINGS) <input type="checkbox"/> SS400 <input type="checkbox"/> SUS304 <input type="checkbox"/> SUS316 <input type="checkbox"/> OTHERS()
NOTE			