

DATE _____

FLOW RELAY [Model LF-B1] INQUIRY CHECKSHEET

Please inform us of the following conditions in detail as much as possible when you make reference to flow relay.

In case of replacing existing flow relay, please describe the serial number inscribed on the nameplate.

Serial number is figures beginning with "7" or "7M".

e.g. MFG № 795081

MFG № 7M15157

MFG № 789652A2

NEW or REPLACEMENT	<input type="checkbox"/> NEW <input type="checkbox"/> REPLACEMENT
MANUFACTURING № (In case of replacement)	MFGNo.7 _____
DIAMETER	<input type="checkbox"/> 15A <input type="checkbox"/> 20A <input type="checkbox"/> 25A <input type="checkbox"/> 32A <input type="checkbox"/> 40A <input type="checkbox"/> 50A
FLANGE STANDARDS	Only JIS5K 40A
FLANGE FACES	Only FF
FLOW DIRECTION	Only DOWNWARD
LIQUID	<input type="checkbox"/> CLEAR WATER <input type="checkbox"/> INDUSTRIAL WATER <input type="checkbox"/> RIVER WATER <input type="checkbox"/> TURBINE OIL
LIQUID TEMPERATURE	60°C or under(TURBINE OIL:+5~60°C)
LIQUID SPECIFIC GRAVITY	
NORMAL FLOWRATE	l/min
MAX FLOWRATE	l/min
OPERATING QUANTITY OF FLOW	<input type="checkbox"/> DECREASE <input type="checkbox"/> INCREASE l/min
MATERIAL	ELEMENT : only C3604(BsBM) BODY : only FC200
BODY COLOUR	<input type="checkbox"/> STANDARD MUNSSELL 7.5BG4/1.5 BAKING FINISH <input type="checkbox"/> OTHERS()
CONTACT RATING (AC60VA,DC60W)	<input type="checkbox"/> AC V A <input type="checkbox"/> DC V A
ACCESSORIES	<input type="checkbox"/> SS400 WELDING FLANGES(with BOLTS&PACKINGS) ※A flange(J5K,40A,FF) of which pipe hole diameter is processed to fit with the connection diameter is attached. Install the flange by welding. <input type="checkbox"/> NO NEED
NOTE	