FLOW RELAY [Model LF-B1] INQUIRY CHECKSHEET

Please inform us of the following conditions in detail as much as possible when you make reference to flow relay.

In case of replacing existing flow relay, please describe the serial number inscribed on the nameplate.

Serial number is figures beginning with "7" or "7M".

e.g. MFG № 795081 MFG № 7M15157 MFG № 789652A2

| NEW or REPLACEMENT | ☐ NEW ☐ REPLACEMENT |
|--------------------------|--|
| MANUFACTURING № | MECNO 7 |
| (In case of replacement) | MFGNo.7 |
| DIAMETER | □15A □20A □25A □32A □40A □50A |
| FLANGE STANDARDS | Only JIS5K 40A |
| FLANGE FACES | Only FF |
| FLOW DIRECTION | Only DOWNWARD |
| LIQUID | □CLEAR WATER □INDUSTRIAL WATER □RIVER WATER □TURBINE OIL |
| LIQUID TEMPERATURE | 60°C or under(TURBINE OIL:+5∼60°C) |
| LIQUID SPECIFIC GRAVITY | |
| NORMAL FLOWRATE | l/min |
| MAX FLOWRATE | l/min |
| OPERATING QUANTITY | □DECREASE □INCREASE l/min |
| OF FLOW | |
| MATERIAL | ELEMENT: only C3604(BsBM) |
| | BODY: only FC200 |
| BODY COLOUR | STANDARD MUNSELL 7.5BG4/1.5 BAKING FINISH |
| CONTACT DATING | OTHERS() |
| CONTACT RATING | □AC V A |
| (AC60VA,DC60W) | DC V A |
| ACCESSORIES | □SS400 WELDING FLANGES(with BOLTS&PACKINGS) |
| | ※A flange(J5K,40A,FF) of which pipe hole diameter is |
| | processed to fit with the connection diameter is attached. |
| | Install the flange by welding. |
| | □NO NEED |
| NOTE | |
| | |
| | |
| | |
| | |